

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 July 2005 (21.07.2005)

PCT

(10) International Publication Number  
**WO 2005/066378 A1**

(51) International Patent Classification<sup>7</sup>: C22B 3/04, 3/02

(21) International Application Number:  
PCT/ZA2005/000002

(22) International Filing Date: 7 January 2005 (07.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2004/0082 7 January 2004 (07.01.2004) ZA  
2004/8476 20 October 2004 (20.10.2004) ZA

(71) Applicant and  
(72) Inventor: DUNN, Grenvil, Marquis [ZA/ZA]; 37  
Maskew Street, Rowhill, 1559 Springs (ZA).

(74) Agent: FISHER, Les, T.; Les Fisher & Co, P.O. Box  
391864, 2018 Bramley (ZA).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,  
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: EXOTHERMIC PRESSURE LEACH AUTOCLAVE CIRCUITS



(57) Abstract: The efficiency of an exothermic autoclave leach process is increased by increasing the retention time of the solids fraction in the feed slurry over that of the liquid fraction. This is achieved by flashing the contents of the first oxidative autoclave compartment to a flash vessel, with the underflow therefrom passing to a thickener and the underflow from the thickener being fed to the autoclave feed tank or any tank upstream of the feed tank. Exothermic heat generated in the first compartment of the autoclave is abstracted in the flashing process. Additionally portions of the overflow from the thickener are returned to the feed tank and fed to the autoclave discharge tank.

WO 2005/066378 A1